

Salt Spray Tester

KOMEG



Application

Corrosion resistance test for products after treated by plating, anodized, spraying, and anti-rust .

Features

- High temperature resistant material imported from Germany to ensure long-term use
- Complete system for water level and water temperature protection to ensure safe use
- Nozzle spray pressure, work room temperature and working time adjustable, easy operation
- Accurate glass nozzle to assure evenly spread and no crystallization block.

Standards implemented and met

- 1 GB/T 2423.17-1993 salt spray test
- 2 GB/T 2423.18-2000 salt spray test
- 3 GB/T 10125-1997 salt spray test
- 4 ASTM.B117-97 salt spray test
- 5 JIS H8502 salt spray test
- 6 IEC68-2-11 salt spray test
- 7 IEC68-2-52 1996 salt spray test
- 8 GB.10587-89 salt spray test
- 9 CNS.4158 salt spray test
- 10 CNS.4159 CASS Copper accelerated acid salt spray test
- 11 GB/T 12967.3-91 CASS Copper accelerated acid salt spray test

Specifications (Note: We reserve the right to change specifications without prior notice)

Model	HL-160-NS	HL-90-BS	HL-60-SS
Interior dimensions(W*H*D)mm	1600*500*1000	900*500*600	600*400*450
Exterior dimensions(W*H*D)mm	2240*1500*1600	1460*1280*910	1130*1070*630
Volume(L)	800	270	60
Heater	15KW+1KW	7KW+0.75KW	3KW+0.75KW
Air compressor	2HP	1/2HP	1/2HP

Temp. range	35°C~50°C
Power	AC220V 1Φ 50Hz